




# GAM851



Dumper Trailer, All Position



Dumper, All Position



Cement Mixer, All Position



Mixed Service

## All Position Mixed Service Tire


### Features

### Benefits



Deep tread design with cut and chip resistant compound

Superb resistance to tread tearing, impacts and casing damage in on/off road conditions



Bold three groove design

Optimized block ratio to provide even wear and reduced noise levels



Enhanced casing construction

Provides improved footprint for excellent handling



3PMSF certified performance

Enhanced traction in mud and snow

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs. @ PSI)	(Lbs. @ PSI)	Inch	Inch	Inch	32nds		Lbs.
385/65R22.5	100EV2130Q	20	J	164/-K (158/-L)	11.75	12.25	9,920@131	—	15.3	19.5	42.2	21	492	170
425/65R22.5	100EV854Q	20	L	165/-K	12.25	11.75 13.00 14.00	11,400@120	—	16.6	20.4	44.3	23	469	197
445/65R22.5	100EV841Q	20	L	169/-K	13.00	12.25 14.00	12,800@131	—	17.5	20.8	45.3	23	459	214

PR Ply Rating   LR Load Range   LI Load Index   SR Speed Rating   RPM Revolutions Per Mile

Product details given for information only. Giti reserves the right to modify details of products and services at any time and without notice.



COMMERCIAL TRUCK TIRES