

Features	Benefits
Special compound with low rolling resistance and low heat generation	Reduced rolling resistance with improved fuel economy
Four zigzag longitudinal groove design	Excellent highway traction and driving stability
Closed shoulder design	Provides excellent high speed performance, longer mileage and minimizes irregular shoulder wear
Optimized block ratio	Uniform block stiffness delivers even wear and long mileage

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs.@ PSI)	(Lbs.@ PSI)	Inch	Inch	Inch	32nds		Lbs.
11R22.5	100EV1780Q	14	G	144/142 L	8.25	7.50	6,175@105	5,840@105	11.0	19.3	41.5	26	501	136
295/75R22.5	100EV1672Q	14	G	144/141 L	9.00	8.25	6,175@110	5,675@110	11.7	18.8	40.2	26	517	125
11R24.5	100EV1446Q	14	G	146/143 L	8.25	7.50	6,610@105	6,005@105	11.0	20.4	43.7	26	475	144
285/75R24.5	100EV1479Q	14	G	144/141 L	8.25	_	6,175@110	5,675@110	11.1	19.5	41.6	26	499	129
PR Ply Rating LR Load Range LI Load Index SR Speed Rating RPM Revolutions Per Mile														

Giti manufactures SmartWay Verified Technologies. Learn more at epa.gov/smartway.

Product details given for information only. Giti reserves the right to modify details of products and services at any time and without notice.

