

Regional Trailer and All Position Light Duty Tire

Features	Benefits
New generation pattern with advanced groove design and extra wide shoulder	Provides excellent shoulder area protection and even footprint for consistent wear
New casing construction	Improved casing strength for exceptional durability and retreadability
Specialized tread compound	Improved tread wear resistance and handling characteristics
3PMSF certified performance (4th Qtr. 2019)	Enhanced traction in mud and snow

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Wheel	Single	Dual	Section Width	Radius	Overall Diameter		RPM	Weight
					Inch	Inch	(Lbs.@ PSI)	(Lbs.@ PSI)	Inch	Inch	Inch	32nds		Lbs.
215/75R17.5	100EV1451Q	16	Н	135/133 J	6.00	6.75	4,805@125	4,450@125	8.3	14.1	30.2	16	688	61
235/75R17.5	100EV2141Q	16	Н	143/141 J (144/144 F)	6.75	7.50	6,005@125	5,675@125	9.2	14.6	31.4	16	662	71
245/70R17.5	100EV871Q	16	Н	143/141 J (146/146 F)	7.50	6.75	6,005@127	5,675@125	9.8	14.3	31.1	17	668	70
385/65R22.5	100EV1740Q	20	L	164 K (158 L)	11.75	12.25	11,000@130	_	15.3	19.5	42.2	20	492	167

PR Ply Rating LR Load Range LI Load Index SR Speed Rating RPM Revolutions Per Mile

