

RECOMMENDED LOAD & INFLATION

RADIAL PLY TIRES FOR TRUCKS, BUSES AND TRAILERS USED IN NORMAL HIGHWAY SERVICE.
TIRES MOUNTED ON 15° DROP CENTER RIMS

Tire Size Designation	Pattern	PR	Use	Tire Load Limits at Various Cold Inflation Pressures (Pressure Listed is the Minimum for the Load)																
				psi	65	70	75	80	85	90	95	100	105	110	115	120	123	125	130	
215/75R17.5	GDR638	14	DUAL	kg		1160	1220	1290	1350	1350	1480	1540	1600 (G) 124							
				lbs		2550	2695	2835	2980	2980	3255	3390	3530 (G)							
			SINGLE	kg		1230	1300	1370	1440	1440	1570	1640	1700 (G) 126							
				lbs		2710	2865	3015	3165	3165	3460	3605	3750 (G)							
215/75R17.5	GTL919	16	DUAL	kg				1450	1520	1520	1650	1720	1790	1860	1910	1990		2060 (H) 133		
				lbs				3195	3350	3350	3645	3795	3945	4095	4220	4390		4540 (H)		
			SINGLE	kg				1530	1610	1610	1750	1820	1900	1960	2040	2110		2180 (H) 135		
				lbs				3375	3540	3540	3860	4010	4180	4330	4995	4650		4805 (H)		
235/75R17.5	GDR638	14	DUAL	kg										1900 (G) 130						
				lbs												4190 (G)				
			SINGLE	kg												2000 (G) 132				
				lbs													4410 (G)			
235/75R17.5	GTL919	16	DUAL	kg		1620	1710	1800	1890	1980	2070	2150	2240	2320	1050	2490		2580 (H) 141		
				lbs		3570	3770	3970	4170	4365	4560	4750	4940	5125	5310	5495		5680 (H)		
			SINGLE	kg		1710	1810	1900	2000	2090	2180	2270	2370	2460	2540	2630		2720 (H) 143		
				lbs		3770	3985	4195	4405	3372	4815	5015	5215	5415	5610	5805		6000 (H)		
245/70R17.5	GTL919	16	DUAL	kg				1965	2035	2105	2165	2235	2305	2375	2435	2505		2575 (H) 141		
				lbs				4331	4485	4639	4772	4926	50890	5235	5367	5521		5675 (H)		
			SINGLE	kg				2115	2185	2255	2315	2385	2455	2525	2585	2655		2725 (H) 143		
				lbs				4661	4816	4970	5102	5257	5411	5565	5697	5852		6005 (H)		
225/70R19.5	GSR225, GDR638	14	DUAL	kg		1170	1220	1290	1360	1430	1490	1560	1630	1700(G)126						
				lbs		2579	2689	2843	2997	3152	3284	3438	3593	3750(G)						
			SINGLE	kg		1270	1320	1390	1460	1530	1590	1660	1730	1800(G)128						
				lbs		2799	2909	3064	3218	3372	3504	3659	3813	3970(G)						
245/70R19.5	GSR225, GDR638	16	DUAL	kg				1580	1650	1720	1780	1850	1920	1990	2050	2120(H)134				
				lbs				3482	3637	3791	3923	4077	4232	4386	4518	4675(H)				
			SINGLE	kg				1700	1770	1840	1900	1970	2040	2110	2170	2240(H)136				
				lbs				3747	3901	4055	4188	4342	4496	4650	4783	4940(H)				
265/70R19.5	GSR225	16	DUAL	kg											2360 (H) 138					
				lbs												5205				
			SINGLE	kg												2500 (H) 140				
				lbs													5510			
10R22.5	GAL817	16	DUAL	kg														2650 (H) 142		
				lbs															5840 (H)	
			SINGLE	kg															2800 (H) 144	
				lbs																6175 (H)
11R22.5	GDL651 FS, GTL922 FS	14	DUAL	kg		2190	2240	2310	2380	2380	2510	2580	2650(G)142							
				lbs		4827	4937	5091	5246	5246	5532	5686	5840(G)							
			SINGLE	kg		2340	2390	2460	2530	2530	2660	2730	2800(G)144							
				lbs		5157	5268	5422	5576	5576	5863	6017	6175(G)							

RECOMMENDED LOAD & INFLATION

RADIAL PLY TIRES FOR TRUCKS, BUSES AND TRAILERS USED IN NORMAL HIGHWAY SERVICE.
TIRES MOUNTED ON 15° DROP CENTER RIMS

Tire Size Designation	Pattern	PR	Use	Tire Load Limits at Various Cold Inflation Pressures (Pressure Listed is the Minimum for the Load)																
				psi	65	70	75	80	85	90	95	100	105	110	115	120	123	125	130	
11R22.5	GDM635	16	DUAL	kg				2185	2255	2325	2385	2455	2525	2595	2655	2725(H)143				
				lbs				4816	4970	5124	5257	5411	5565	5719	5852	6005(H)				
			SINGLE	kg				2460	2530	2600	2660	2730	2800	2870	2930	3000(H)146				
				lbs				5422	5576	5730	5863	6017	6171	6325	6458	6610(H)				
11R22.5	GDM686, GAM835, GDR621, GDR652, GT 867	16	DUAL	kg				2260	2330	2400	2460	2530	2600	2670	2730	2800(H)144				
				lbs				4981	5135	5290	5422	5576	5730	5885	6017	6175(H)				
			SINGLE	kg				2610	2680	2750	2810	2880	2950	3020	3080	3150(H)148				
				lbs				5752	5907	6061	6193	6348	6502	6656	6788	6940(H)				
12R22.5	GDM686	16	DUAL	kg						2680	2740	2810	2880	2950	3010	3080	3150(H)148			
				lbs						5907	6039	6193	6348	6502	6634	6788	6940(H)			
			SINGLE	kg							3080	3140	3210	3280	3350	3410	3480	3550(H)152		
				lbs							6788	6921	7075	7229	7383	7516	7670	7830(H)		
255/70R22.5	GTL922 FS, GAL817	16	DUAL	kg				1760	1830	1900	1960	2030	2100	2170	2230	2300(H)137				
				lbs				3879	4033	4188	4320	4474	4628	4783	4915	5070(H)				
			SINGLE	kg				1960	2030	2100	2160	2230	2300	2370	2430	2500(H)140				
				lbs				4320	4474	4628	4761	4915	5069	5223	5356	5510(H)				
275/70R22.5	GSR225, GT867	16	DUAL	kg		1770	1870	1970	2060	2160	2260	2350	2440	2540	2630	2720		2810	2900 (H) 145	
				lbs		3895	4115	4335	4550	4765	4975	5180	5390	5590	5795	5995		6195	6395 (H)	
			SINGLE	kg		1920	2030	2180	2240	2350	2450	2550	2650	2760	2860	2950			3052	3150 (H) 148
				lbs		4230	4470	4705	4940	5175	5400	5630	5850	6075	6295	6510			6730	6945 (H)
295/75R22.5	GSL229 FS, GTL922 FS, GDL651 FS, GSR231 FS, GDR652	14	DUAL	kg		1860	1950	2060	2130	2220	2300	2390	2470	2575(G)141						
				lbs		4099	4298	4540	4695	4893	5069	5268	5444	5675(G)						
			SINGLE	kg		2040	2140	2240	2340	2440	2500	2620	2710	2800(G)144						
				lbs		4496	4717	4937	5157	5378	5510	5774	5973	6175(G)						
295/80R22.5	GT867	18	DUAL	kg			2200	2300	2400	2500	2690	2690	2790	2900	2980	3075 (H) 147		3150	3250 (J) 149	
				lbs			4860	5070	5305	5525	5945	5945	6150	5395	6550	6780 (H)		6950	7160 (J)	
			SINGLE	kg			2420	2500	2640	2750	2960	2960	3070	3150	3270	3350 (H) 150		3460	3550 (J) 152	
				lbs			5340	5510	5830	6070	6535	6535	6760	6940	7200	7390 (H)		7640	7830 (J)	
315/80R22.5	GDR621 GT686	18	DUAL	kg				2575	2650	2750	2900	2970	3070	3150	3270	3450(J)151				
				lbs				5675	5841	6061	6392	6546	6766	6943	7207	7610(J)				
			SINGLE	kg				2800	2910	3030	3150	3260	3370	3450	3590	3750(J)154				
				lbs				6171	6414	6678	6943	7185	7427	7604	7912	8270(J)				
315/80R22.5	GSR225	20	DUAL	kg			2420	2575	2650	2750	2900 (G) 145	2970	3070	3150 (H) 148	3270	3450 (J) 151		3590	3750 (L) 154	
				lbs			5345	5675	5840	6070	6395 (G)	6545	6770	6940 (H)	7210	7610 (J)		7910	8270 (L)	
			SINGLE	kg			2660	2800	2910	3030	3150 (G) 148	3260	3370	3450 (H) 151	3590	3750 (J) 154		3940	4125 (L) 157	
				lbs			5875	6175	6415	6670	6940 (G)	7190	7440	7610 (H)	7920	8270 (J)		8690	9090 (L)	
315/80R22.5	GAM835	22	DUAL	kg														4123		
				lbs															9090	
			SINGLE	kg																4627
				lbs																10200

RECOMMENDED LOAD & INFLATION

RADIAL PLY TIRES FOR TRUCKS, BUSES AND TRAILERS USED IN NORMAL HIGHWAY SERVICE.
TIRES MOUNTED ON 15° DROP CENTER RIMS

Tire Size Designation	Pattern	PR	Use	Tire Load Limits at Various Cold Inflation Pressures (Pressure Listed is the Minimum for the Load)																
				psi	65	70	75	80	85	90	95	100	105	110	115	120	123	125	130	
385/65R22.5	GAM851	18	DUAL	kg																
				lbs																
			SINGLE	kg	2750	2880	3060	3150	3350	3470	3650	3740	3850	4000	4100	4250 (J) 158				
				lbs	6060	6380	6720	6940	7350	7650	8050	8230	8510	8820	9050	9370 (J)				
385/65R22.5	GTL919	20	DUAL	kg																
				lbs																
			SINGLE	kg			3060	3150	3350	3470	3650	3740	3850	4000	4100	4250		4340	4500 (L) 160	
				lbs			6720	6940	7350	7650	8050	8230	8510	8820	9050	9370		9610	9920 (L)	
425/65R22.5	GAM851	20	DUAL	kg																
				lbs																
			SINGLE	kg	3270	3430	3640	3750	3980	4130	4250	4440	4580	4750 (J) 162	4880	5150 (L) 165				
				lbs	7210	7590	7990	8270	8740	9100	9370	9790	10100	10500 (J)	10700	11400 (L)				
445/50R22.5	GDL633 FS	20	DUAL	kg																
				lbs																
			SINGLE	kg	2800	2980	3150	3320	3480	3640	3810	3970	4120	4250 (J) 158	4430	4625 (L) 161				
				lbs	6175	6570	6940	7310	7680	8030	8390	8740	9090	9370 (J)	9780	10200 (L)				
445/65R22.5	GAM851	20	DUAL	kg																
				lbs																
			SINGLE	kg	3540	3720	2950	4125	4320	4470	4620 (H) 161	4820	4960	5150	5290	5600 (L) 168				
				lbs	7800	8230	8660	9090	9480	9870	10200 (H)	10600	11000	11400	11700	12300 (L)				
11R24.5	GDL651 FS, GTL922 FS, GDR652	14	DUAL	kg		2265	2315	2385	2455	2525	2585	2655	2725(G)143							
				lbs		4992	5102	5257	5411	5565	5697	5852	6005(G)							
			SINGLE	kg		2540	2590	2660	2730	2800	2860	2930	3000(G)146							
				lbs		5598	5708	5863	6017	6171	6303	6458	6610(G)							
11R24.5	GDL651 FS, GTL922 FS, GDR652	14	DUAL	kg		2110	2210	2300	2390	2500 (F) 138	2580	2660	2725 (G) 143							
				lbs		4660	4870	5070	5260	5510 (F)	5675	5840	6005 (G)							
			SINGLE	kg		2190	2300	2410	2520	2650 (F) 142	2770	2890	3000 (G) 146							
				lbs		4820	5070	5310	5550	5840 (F)	6095	6350	6610 (G)							
11R24.5	GDR652, GDR621, GAM835, GDM635	16	DUAL	kg				2460	2530	2600	2660	2730	2800	2870	2930	3000(H)146				
				lbs				5422	5576	5730	5863	6017	6171	6325	6458	6610(H)				
			SINGLE	kg				2710	2780	2850	2910	2980	3050	3120	3180	3250(H)149				
				lbs				5973	6127	6281	6414	6568	6722	6876	7009	7160(H)				
11R24.5	GDR652, GDR621, GAM835, GDM635	16	DUAL	kg		2110	2210	2300	2390	2500 (F) 138	2580	2660	2725 (G) 143	2820	2910	3000 (H) 146				
				lbs		4660	4870	5070	5260	5510 (F)	5675	5840	6005 (G)	6205	6405	6610 (H)				
			SINGLE	kg		2190	2300	2410	2520	2650 (F) 142	2770	2890	3000 (G) 146	3080	3160	3250 (H) 149				
				lbs		4820	5070	5310	5550	5840 (F)	6095	6350	6610 (G)	6790	6970	7160 (H)				
285/75R24.5	GDL651 FS, GTL922 FS, GDR652	14	DUAL	kg		1870	1970	2060	2150	2240	2360	2410	2490	2575(G)141						
				lbs		4121	4342	4540	4739	4937	5201	5312	5488	5675(G)						
			SINGLE	kg		2060	2160	2240	2360	2460	2575	2650	2740	2800(G)144						
				lbs		4540	4761	4937	5201	5422	5675	5841	6039	6175(G)						